



- Push and pull test
- Units: N, gf, kgf, ozf, lbf
- 500 memories
- Automatic power off
- Metal case
- LCD display with backlight, can turn 180°
- Overload alarm



ISF-1DF100

SPECIFICATION

| Code | ISF-1DF10 | ISF-1DF50 | ISF-1DF100 | ISF-1DF500 | ISF-1DF1000 |
|-------------------|---|-----------|------------|------------|-------------|
| Load capacity (N) | 10 | 50 | 100 | 500 | 1000 |
| Resolution (N) | 0.01 | 0.01 | 0.1 | 0.1 | 1 |
| Accuracy | ±0.3% (of load capacity) | | | | |
| Measuring mode | tracking, peak (max.), low and high limits with judgement | | | | |
| Power supply | built-in rechargeable battery | | | | |
| Dimension | 150×73×33mm | | | | |
| Weight | 450g | | | | |

printer (optional)

DIGITAL FORCE GAGE





STANDARD DELIVERY

| Main unit | 1pc |
|------------------------|--|
| AC/DC adapter | 1pc |
| USB cable and software | 1pc |
| Push/pull accessory | 6pcs (flat push tip, V push tip, knife-edge push tip, point push tip, pull clamp, extension rod) |

OPTIONAL ACCESSORY

| Printer | ISF-DF-PRINTER |
|------------|----------------|
| Test stand | ISF-MT1K |