

**DATA
OUTPUT**

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable
(code **7306-20**, **7302-SPC5A/SPC5B**, **7305-SPC2A**)

DIGITAL CALIPERS (STANDARD MODEL)


**INSPECTION
CERTIFICATE**
TRACEABLE TO DKD



1108-150

(mm)

| Code | Range | Accuracy | Thumb roller | L | a | b | c | d |
|--------------------|---------------|----------|--------------|-----|----|------|----|----|
| 1108-150 * | 0-150mm/0-6" | ±0.02mm | with | 236 | 21 | 16 | 16 | 40 |
| 1108-200 * | 0-200mm/0-8" | ±0.03mm | with | 286 | 24 | 19 | 16 | 50 |
| 1108-250 * | 0-250mm/0-10" | ±0.03mm | with | 350 | 25 | 20.5 | 16 | 60 |
| 1108-300 * | 0-300mm/0-12" | ±0.03mm | with | 400 | 25 | 20.5 | 16 | 60 |
| 1108-150W * | 0-150mm/0-6" | ±0.02mm | without | 236 | 21 | 16 | 16 | 40 |
| 1108-200W * | 0-200mm/0-8" | ±0.03mm | without | 286 | 24 | 19 | 16 | 50 |
| 1108-250W * | 0-250mm/0-10" | ±0.03mm | without | 350 | 25 | 20.5 | 16 | 60 |
| 1108-300W * | 0-300mm/0-12" | ±0.03mm | without | 400 | 25 | 20.5 | 16 | 60 |



* Supplied with manufacturer inspection certificate traceable to DKD Germany