






**ISV-MS726** 





bend in any direction





360° swivel in clockwise and counter-clockwise

bend within  $\alpha$ 

## **SPECIFICATION**

Code		ISV-MS716	ISV-MS726	ISV-MS736	ISV-MS714	ISV-MS724	ISV-MS734
Lens	diameter (D)	6.5mm 4.5mm					
	lens bending range (α)	±160°			±120°		
	focus distance (F)	15mm~∞ 8~80mm					
	viewing angle (θ)	>120°					
	illumination	6 pcs LED					
	pixel	0.92M					
	resolution	1280x720					
	dust/waterproof	IP64					
	bend control	manual joystick					
Cable	length	1m	1.5m	3m	1m	1.5m	3m
	type	tungsten wire weaved cable					
Main unit	function	take picture, take video					
	file format	picture: JPG, video: AVI					
	image process	brightness, image quality zoom (1X, 1.5X, 2X, 2.5X, 3X)					
	memory	32G SD card					
	output	TV, USB, HDMI					
	temperature sensing	display real-time temperature of the probe					
	screen rotation	180°					
	power supply	rechargeable battery (for 4 hours working) AC/DC adapter (for continuous working)					
Weight		600g	650g	800g	550g	600g	700g

connect to 13.3" high-definition display (with stand and HDMI cable) (optional)



## STANDARD DELIVERY

•					
Main unit	1 pc				
Cable with lens	1 pc				
32G SD card	1 pc				
AC/DC adapter	1 pc				
Video output cable	1 pc				
USB cable	1 pc				

## **OPTIONAL ACCESSORY**