

# DIGITAL INSIDE GROOVE CALIPERS

preset buttons



**1120-150A**  
type A



**1120-150P**  
type C





**1120-150B**  
type B



**1120-150D**  
type D

- Measure groove diameter
- Resolution: 0.01mm/0.0005"
- Buttons type A: on/off, set, mm/inch, preset (+, -),  
type B: on/off, zero, mm/inch,  
type C: on/off, zero, mm/inch, ABS/REL, hold  
type D: on/off, set, mm/inch, preset
- Battery CR2032
- Made of stainless steel
- Optional accessory: depth stop  
(code **6143**, for calipers with c=16mm)

depth stop **6143**  
(optional)



No dust/waterproof, preset, no need to add the width of the jaws on the reading, with data interface  
(data output cable code 7315-21, 7302-21, optional)

Code	Range	Type	Accuracy	L	a	b	c	d	e	f
1120-150A	22-150mm/0.87-6"	A	±0.04mm	250mm	5mm	11mm	16mm	30mm	1mm	4mm
1120-1501	35-150mm/1.38-6"	A	±0.06mm	250mm	6mm	17.5mm	16mm	60mm	1.5mm	4mm
1120-200A	25-200mm/0.98-8"	A	±0.04mm	310mm	5mm	12.5mm	16mm	40mm	1mm	4mm
1120-2001	40-200mm/1.57-8"	A	±0.06mm	310mm	7mm	20mm	16mm	70mm	2.5mm	4mm
1120-300A	30-300mm/1.18-12"	A	±0.05mm	410mm	5mm	15mm	16mm	50mm	1.5mm	4mm
1120-3001	50-300mm/1.97-12"	A	±0.07mm	410mm	8mm	25mm	16mm	80mm	2.5mm	4mm
1120-500	40-500mm/1.57-20"	A	±0.07mm	680mm	5mm	20mm	24mm	90mm	2.2mm	4mm
1120-5001	60-500mm/2.36-20"	A	±0.08mm	680mm	10mm	30mm	24mm	120mm	3.4mm	4mm
1120-5002	80-500mm/3.15-20"	A	±0.08mm	680mm	16mm	40mm	24mm	150mm	5.2mm	4mm

No dust/waterproof, preset, no need to add the width of the jaws on the reading, built-in wireless  
(receiver code 7315-2 or 7315-3 is required)

Code	Range	Type	Accuracy	L	a	b	c	d	e	f
1120-150AWL	22-150mm/0.87-6"	A	±0.04mm	250mm	5mm	11mm	16mm	30mm	1mm	4mm
1120-1501WL	35-150mm/1.38-6"	A	±0.06mm	250mm	6mm	17.5mm	16mm	60mm	1.5mm	4mm
1120-200AWL	25-200mm/0.98-8"	A	±0.04mm	310mm	5mm	12.5mm	16mm	40mm	1mm	4mm
1120-2001WL	40-200mm/1.57-8"	A	±0.06mm	310mm	7mm	20mm	16mm	70mm	2.5mm	4mm
1120-300AWL	30-300mm/1.18-12"	A	±0.05mm	410mm	5mm	15mm	16mm	50mm	1.5mm	4mm
1120-3001WL	50-300mm/1.97-12"	A	±0.07mm	410mm	8mm	25mm	16mm	80mm	2.5mm	4mm
1120-500WL	40-500mm/1.57-20"	A	±0.07mm	680mm	5mm	20mm	24mm	90mm	2.2mm	4mm
1120-5001WL	60-500mm/2.36-20"	A	±0.08mm	680mm	10mm	30mm	24mm	120mm	3.4mm	4mm
1120-5002WL	80-500mm/3.15-20"	A	±0.08mm	680mm	16mm	40mm	24mm	150mm	5.2mm	4mm

No dust/waterproof, no preset, need to add the width of the jaws on the reading

Code	Range	Type	Accuracy	L	a	b	c	d	e	f
1120-150B	50-150mm/1.97-6"	B	±0.06mm	270mm	8mm	25mm	20mm	90mm	3.4mm	4mm
1120-200B	60-200mm/2.36-8"	B	±0.06mm	320mm	10mm	30mm	20mm	100mm	3.4mm	4mm
1120-300B	60-300mm/2.36-12"	B	±0.07mm	420mm	10mm	30mm	20mm	110mm	3.4mm	4mm

**IP67 dust/waterproof, without data interface, no automatic power off, set zero after power on each time, no preset, need to add the width of the jaws on the reading**

Code	Range	Type	Accuracy	L	a	b	c	d	e	f
<b>1120-150P</b>	22-150mm/0.87-6"	C	±0.04mm	250mm	5mm	11mm	16mm	30mm	1mm	4mm

**IP67 dust/waterproof, without data interface, preset, no need to add the width of the jaws on the reading**

Code	Range	Type	Accuracy	L	a	b	c	d	e	f
<b>1120-150D</b>	20-150mm/0.78-6"	D	±0.04mm	235mm	4mm	10mm	16mm	30mm	1.2mm	3.5mm
<b>1120-200D</b>	25-200mm/0.98-8"	D	±0.04mm	287mm	5mm	12mm	16mm	40mm	1.2mm	3.5mm
<b>1120-300D</b>	30-300mm/1.08-12"	D	±0.05mm	390mm	5mm	15mm	16mm	50mm	1.5mm	3.5mm

**IP67 dust/waterproof, built in bluetooth, preset, no need to add the width of the jaws on the reading**

Code	Range	Type	Accuracy	L	a	b	c	d	e	f
<b>1120-150DWL</b>	20-150mm/0.78-6"	D	±0.04mm	235mm	4mm	10mm	16mm	30mm	1.2mm	3.5mm
<b>1120-200DWL</b>	25-200mm/0.98-8"	D	±0.04mm	287mm	5mm	12mm	16mm	40mm	1.2mm	3.5mm
<b>1120-300DWL</b>	30-300mm/1.08-12"	D	±0.05mm	390mm	5mm	15mm	16mm	50mm	1.5mm	3.5mm