DIGITAL MEASURING MICROSCOPES (WITH DISPLAY)




ISM-DL300 (without contour illumination)







ATTENTION: PLEASE MAKE CONFOCAL ADJUSTMENT AFTER CHANGING CAMERA ADAPTERS OR AUXILIARY OBJECTIVES



ISM-DL301 (with contour illumination)



17

- 1080P high-definition image
- Built-in software without computer, operated by mouse
- Take pictures, save to USB flash disk
- Measurement results can be sent to Excel
- Automatic white balance and exposure
- Brightness, contrast ratio, gain are adjustable



0.5X camera adapter



1X auxiliary objective (included)



1X camera adapter (optional)



calibration plate (included)



16G USB flash disk (included)



2X auxiliary objective (optional)



(optional) (X-Y travel: 74×60mm)

SPECIFICATION

SPECIFICATION		
Code	ISM-DL300 (without contour illumination)	ISM-DL301** (with contour illumination)
Magnification	15X~100X	
Sensor	1/2" CMOS	
Pixel	2M	
Resolution	1920×1080	
Frame rate	60fps	
Output	HDMI	
Power supply	power adapter	power adapter and 220V, 50/60Hz**
Dimension (L×W×H)	570×300×430mm	
Weight	6.5kg	

^{**}Add "-U" on code No. when power supply is 110V, 50/60Hz

STANDARD DELIVERY

V 17 111-27 111-27 21-21 21 21 21 21 21 21 21 21 21 21 21 21 2		
Main unit	1 pc	
0.5X camera adapter	1 pc	
1X auxiliary objective	1 pc	
Calibration plate	1 pc	
16G USB flash disk	1 pc	
White/black plate	1 pc	
Mouse	1 pc	
HDMI cable	1 pc	
Power adapter	2 pcs	

OPTIONAL ACCESSORY

OI HONAL ACCESSORY		
1X camera adapter	ISM-DL-CA1X	
2X auxiliary objective	ISM-DL-OB2X	
X-Y glass stage (travel: 74×60mm)	ISM-DL-STAGE	
X-Y metal stage	ISM-DL-STAGE1	
LED auxiliary illumination	ISM-DL-LED	
Coaxial light illumination	ISM-DL-COAXIAL	
Auxiliary objective	page 258	

To be continued