

# PORTABLE LEEB HARDNESS TESTER CODE HDT-LP200



- Can change probes
- Dual-coil probe for high accuracy
- Universal testing angle, no need to set impact direction
- Based on Leeb (HLD), converted to Vickers (HV), Brinell (HB), Rockwell (HRC, HRA and HRB), Shore (HS) and tensile strength (SGM)
- Dual value display, shows both Leeb and converted hardness
- Large LCD display with backlight
- Can choose large font display and statistics display
- Automatically calculate maximum, minimum and average value
- Save 300 data
- Operating temperature: -10°C~45°C
- According to ASTM A956, DIN 50156, GB/T 17394



printer  
(optional)



hardness test  
block D (included)



small support ring  
(included)

## SPECIFICATION

Resolution	1HLD/1HV/1HB/0.1HRC/0.1HRB/0.1HRA/0.1HS/1SGM
Accuracy	±2HLD/±0.3% (when HLD=800)
Measuring range	HL 100-960/HRC 0.9-79.2/HRB 1-140/HB 1-1878/HV 1-1698 HS 0.5-1370/HRA 1-88.5/SGM (rm) 1-6599N/mm <sup>2</sup>
Power supply	2xAAA battery
Dimension	127×67×30mm
Weight	240g


## STANDARD DELIVERY

Main unit	1pc
Hardness test block D	1pc
Small support ring	1pc
Cleaning brush	1pc
Impact device D	1pc


## OPTIONAL ACCESSORY

Impact device DC	HDT-LP200-DC
Impact device C	HDT-LP200-C
Impact device D+15	HDT-LP200-D15
Impact device DL	HDT-LP200-DL
Impact device E	HDT-LP200-E
Impact device G	HDT-LP200-G
Hardness test block D*	ISH-BHLD
Hardness test block G*	ISH-BHLG
Printer	ISH-LP200-PRINTER
Support rings	see details

\* Hardness test block G (ISH-BHLG) is for impact device G (ISH-LP200-G).  
Hardness test block D (ISH-BHLD) is for all others impact devices.



large font display



statistics display



DC  
(optional)

C  
(optional)

D  
(included)

D+15  
(optional)

DL  
(optional)

E  
(optional)

G  
(optional)

## APPLICABLE WORKPIECE

Impact device	DC	C	D	D+15	DL	E	G
Application	inner wall of small space	small or thin workpiece, coating layer	general use	deep groove	narrow slot or small hole	very hard material	casting or forging workpiece
Maximum roughness of workpiece (Ra)	2μm	0.4μm	2μm	2μm	2μm	2μm	7μm
Minimum weight of workpiece	direct measurement	5kg	1.5kg	5kg	5kg	5kg	15kg
	on solid support	2kg	0.5kg	2kg	2kg	2kg	5kg
	coupled on plate	0.05kg	0.02kg	0.05kg	0.1kg	0.05kg	0.5kg
Minimum thickness of workpiece	3mm	1mm	3mm	3mm	3mm	3mm	10mm