



- ◆ Auto focus
- ◆ High frame rate, without any delay in quick movement
- ◆ Automatic exposure, white balance
- ◆ With measuring functions



DVM4000S

SPECIFICATION

| Code | | DVM4000 | DVM4000S |
|---------------------|------------|----------------------|-----------------------|
| Display | | without | with 21.5" HD monitor |
| Objective | | 0.7X ~ 4.5X | |
| Total magnification | | 26.5X~170X | |
| Max.view field | | 19mmx10.8mm | |
| Working distance | | 100mm | |
| Camera | Pixel | 2M | |
| | Resolution | 1920x1080 | |
| | Frame rate | 60fps | |
| Illumination | | LED adjustable light | |
| Base size | | 380mmx260mm(LxW) | |
| Weight | | 5.7kg | |

INCLUDED ACCESSORIES

| | |
|------------------|-----|
| Main unit | 1pc |
| Stand | 1pc |
| Calibration rule | 1pc |
| AC/DC adapter | 1pc |
| U-disk | 1pc |
| Mouse | 1pc |

OPTIONAL ACCESSORIES

| | |
|---------------------------|-----------|
| X-Y stage(range: 76x65mm) | DVM-STAGE |
| 0.5X objective | DVM-05-O |
| 2X objective | DVM-20-O |